



DASH NO.	THREAD [T] PER AS 1370	SPLINE DASH NO.	A		B		C		D		E	H h14		S	V	Y	Z	APPROX MASS kg/100
			MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN								
050	MJ5x0,8- 4H6H	07	9,1	8,3	7,22	5,8	5,2	5,4	7,00	6,64	1,3	1,8	0,10	0,13	0,182			
060	MJ6x1,0- 4H5H	08	10,6	9,8	8,26	7,1	6,3	5,7	8,10	7,74	1,4	1,8	0,10	0,15	0,256			
070	MJ7x1,0- 4H5H	09	12,1	11,3	9,31	8,1	7,3	6,7	9,10	8,74	2,0	1,8	0,10	0,18	0,340			
080	MJ8x1,0- 4H5H	10	13,6	12,8	10,36	9,1	8,3	7,9	10,40	9,97	2,7	1,8	0,10	0,20	0,450			
100	MJ10x1,25-4H5H	12	16,7	15,7	12,44	11,1	10,3	10,0	13,00	12,57	3,1	2,0	0,13	0,25	0,755			
120	MJ12x1,25-4H5H	15	19,9	18,8	15,54	13,1	12,3	12,0	15,00	14,57	3,5	2,6	0,13	0,30	1,434			

DIMENSIONS IN MILLIMETERS

MATERIAL: WASPALOY PER AMS 5706 OR AMS 5708.

HARDNESS: Rc.32 -42 OR EQUIVALENT.

FINISH: SILVER PLATED PER AMS 2411.

PERFORMANCE: MA 1943.

INSPECTION: FLUORESCENT PENETRANT INSPECTED PER AMS 2645.

NOTES:

- "C" DIA APPLIES AFTER FORMING SELF-LOCKING DEVICE.
- PART IS INTERCHANGEABLE WITH METRIC AEROSPACE STANDARD MA 3429.

TOLERANCES: UNLESS OTHERWISE SPECIFIED: DECIMALS ±0,38 ANGLES ± 2° VENDOR CODE IDENT NO. 27238

BRISTOL INDUSTRIES 630 EAST LAMBERT RD. BREA, CALIFORNIA 92621 (714) 990-4121

TITLE
NUT - SELF-LOCKING, SPLINE DRIVE, WASPALOY
METRIC

PART NUMBER
BHM00736

REVISED

APPROVAL DATE F.M.q. / JB